

Terminal Tractor/Yard Spotter

Used Yard Spotter El Monte - Tow tractors, sometimes call towing tractors or tow tugs, are vehicles used in transporting loads horizontally in warehouses, manufacturing plants, airports, arenas and other large facilities. They are capable of towing several trailers in a train formation. Tow tractors can move aircraft into and outside of airport locations such as terminals and hangars. The tractive effort concept is how loads move from place to place. Tractive effort is the amount of traction a unit has on the ground. Tractive effort says that the heavier the load, the more tractive effort is required. The tow tractor lifts a portion of the load during towing while ensuring the wheels on the load still remain on the ground. The hydraulic mast on the tow tractor is responsible for lifting the load. It produces downforce on the drive wheel underneath to increase the tractive effort. Traction allows the machine to deliver very large and heavy loads. Types of Tow Tractors

There are two basic types of tow tractors: 1. Load carriers; and 2. Heavy-duty tow tractors; Load Carriers

Many industries including airport baggage divisions, manufacturing, parcel transportation and e-commerce rely on moving items of various sizes to and from different locations. Tow tugs or load carrier tow tractors are excellent for these jobs as they can maneuver single items stacked on wheeled platforms for streamlined transport. Load carrier tow tractor models are categorized in the material handling equipment that covers cranes, forklifts and pallet jacks. Load carrier tow tugs transport loads at ground level only, rather than lifting or lowering off the ground or from shelving or other hard to reach areas. Therefore, the load must already be on wheels or on a wheeled platform, ready to be transported. The wheeled platforms are called bogies, trollies or skates. The tow tractor attaches to the trolley and operates similarly to how train cars are attached to a locomotive. Generally, the steel coupling on the tow tug's male-end joins to the front trolley's female-end. The trolley's back portion has a male-end steel coupling that can be used to connect a variety of trollies to a single tug. These machines can transport a variety of items in varying conditions. Trolley types differ to provide customization options. Most trollies types are compatible with each other, meaning they can be connected together. Different kinds of trollies can be maneuvered in a single train, creating flexible transport options. A key benefit of using a load carrier tow tractor is that operators can enjoy a clear view instead of relying on forklifts. Load carrier tow tractors transport trollies in a forward direction which decreases the safety concerns common with reverse forklift operations. This is vital for safety-sensitive places including airports and manufacturing facilities. Towing solutions are a good alternative to traditional forklifts to handle many single items. They are safe and easy to maneuver. A key benefit of these units is that typically, the operator doesn't need a license. Tow tractor operators do not need licenses since they don't lift loads off of the ground. There are three kinds of load carrier tow tractor units to choose from; pedestrian, stand-in and rider-seated. Pedestrian Tow Tractors Pedestrian tow tractors go by many names including electric tow tractor, electric tug, or electric tugger. These units are walk-behind models that move wheeled loads. It is compact, maneuverable and easy to use. Stand-in Tow Tractors Stand-in tow tractors are the most popular design for industries that involve order picking and horizontal transport in manufacturing. Stand-in tow tractors feature a tinier footprint compared to rider-seated editions and they offer a safe driver platform. Rider-Seated Tow Tractors Rider-seated tow tractors are similar to stand-in models except they offer a seated platform for the operator. These types of load carrier tow tractors are popular where loads are transported over longer distances, such as airport baggage systems where checked baggage is transported from the check-in counter at the front of an airport to the aircraft at the terminal, often a great distance from one another. Rider fatigue is decreased with sit-down units for more efficiency and productivity. Heavy Duty Tow Tractors The pushback concept is commonly used in aviation for cargo and large passenger planes. Pushback refers to the process of pushing an aircraft back from an airport terminal by some means other than the aircraft's own power. This pushback process is done by using specially designed heavy duty tow tractors called pushback tractors or pushback tugs. Pushback tugs feature a low-profile enabling them to travel under

the aircraft's nose for easy attachment. Because of the added heavy weight of the aircraft, these tow tractors must be heavy enough to retain enough traction on the ground in order to move the aircraft. Large aircraft tractors can weigh as much as fifty-four tons. These models have a driver's cab that has the option of being raised or lowered during reverse for better visibility. While the vehicle is referred to as a pushback tug or pushback tow tractor, it is also used to tow aircraft in areas where taxiing the aircraft is not practical or safe, such as moving large aircraft in and out of maintenance hangars. The pushback tow tractors come in two subtypes, the towbarless and the conventional.

Conventional Pushback Tow Tractors These units use a tow bar to attach the tug to the nose landing gear on the aircraft. The tow bar is laterally fixed at the nose landing gear; however, it is possible to make height adjustments with slight vertical movements. At the end that attaches to the tug, the tow bar may pivot freely laterally and vertically. Acting like a giant lever, the tow bar can rotate the nose landing gear. Every aircraft has a special tow fitting and the towbar functions as an adapter between the fitting on the landing gear and the standard-sized tow pin. Heavy-duty towbars required for sizeable aircraft ride on their own wheels when they are disconnected from the machine. Attached to the wheels, the hydraulic jacking mechanism allows the towbar to lift to the proper height to mate with the aircraft and tug. The same mechanism is employed in reverse to raise the towbar wheels off the ground for pushback. The towbar can be connected at the front or the rear of the tractor, depending on whether the aircraft will be pushed or pulled.

Towbarless Pushback Tow Tractors Towbarless tractors work without a towbar and scoop up the aircrafts' nose landing gear to lift it off of the ground instead. This design facilitates higher speeds greater aircraft control and can eliminate the necessity of having a worker inside of the cockpit to apply the brakes. As there is no need to maintain numerous towbars, simplicity is the main advantage of this unit. By connecting the tug directly to the aircraft's landing gear tug operators have better control and responsiveness when maneuvering.